## Conference Room audio & Video System

Description	Qty.
Minimum Specifications.	
55" Full-HD Video Wall Display Unit (Ultra Narrow Bezel 3.5mm)	
Specification	
> Industrial level DID LCD panel, suitable for extensive 7×24 continuous works > Ultra-narrow side LCD patchwork	Service and
> High contrast and high brightness greatly enhance the video layering, and present the details of the video	Office
> High fidelity digital processing, brilliant and vivid video > Built-in 3D COMB filter and 3D Noise Reduction	04 + 04 =
> Abundant interfaces HDMI, DVI, VGA, BNC, support video loop > Built-in picture splicing function	For HD & MD Office
> Infrared, RS232 double mode, supporting remote PC control > Fan smart detection, OSD prompt	Office
> Brightness smart detection, power-saving > Using Tamper-proof metal housing, no radiation	707
> Professional thermal design to extend equipment lifespan > Built-in power, low energy consumption, ultra-quiet	Office
> Fast stack installation, professional project design, supporting arc-shaped mounting > Widely used in MCC(monitor command center), Dispatching Platform, Safe City	01+61 = 0
Diagonal: 55"(16:9), Type: PID(FHD), Resolution: 1920×1080, Dot Pitch: 0.63(H)×0.63(V), Physical Seam: 3.5mm, Backlight: LED Luminance(Standard): 500 cd/m², Contrast: 4000:1, View	THO A RE
Angle(Horizontal/Vertical): 178/178, Response Time: 8ms  Gamut(CIE1931): 72%	18+18+1
Or Equivalent	For
Aluminum Back Bracket for Each Screen	04+04=08 For HD & MD
Aluminum Base for Display Unit 55"	Office 04+04= 08 For

----

Processor Speed 2.001	
Processor Speed 3.6 GHz Max Turbo Frequency 4.2 GHz	
Processor Bits 64	
Processor Threads 4	
No of Cores Quad-Core	
L3 cache 8MB RAM size 8GB	
STORAGE Hard drive size 1TB	
Memory card reader Yes	
GRAPHICS CARD	
Dedicated graphics memory	
Graphics memory 4GB	
Graphics processor AMD Radeon R7 450	
Keyboard & Mouse	
High Quality HDMI/DVI Cables for connection between LCD Display Unit and Video Wal Decoder.	04+04 =02
occour.	For
	HD & MD
2///	Office
2KVA UPS with 2 Units of 100AMP Maintenance Free Dry Battery For	
Central Control Room	01+01=02
	For
	HD & MD
	Office
An Supple Asking the Control of the	01+01 =02
Conference System Controller with recording and SD, 30 unit capacity	For
and 02, 00 difficulty	HD & MD
	Office
	Office
A Michigan Translated Commission	01+01 = 02
Discussion Chairman Unit ( High quality )	F
· · · · · · · · · · · · · · · · · · ·	For
	HD & MD
	Office
The second secon	18+18 = 36
Discussion Delegate Unit ( High quality )	
A Company of the second	For
	HD & MD
2 17.7 Gen. 71 for Software of video wall	Office
Service Report 1	04+04=08
ndoor Column Speaker, 5W-10W, 100V, wooden body High Quality	01.04-08
Constitution of the second of	For



	HD & MD Office
Professional FULL HD Video Controller H.265 Supported with 4	Office
Inputs and 04 Output HDMI Ports	
Specifications:	HO-8 MC
19" standard 4U ATCA industry box	
Easy and flexible configuration with pluggable card module design      With 1 Input Card Support up to 4 CILLIDAN Interference	02 0
With 1 Input Card Support up to 4 CH HDMI Interface	01+01 =08
With 3 Output Card support up to 18 Screens on HDMI Interface  (95-b-@10909.H-355 (H-354 december))	
(96ch@1080P H.265/H.264 decoding)	For
• Support Resolution 4096*2160@30fps,3840*2160@30fps,	HD & MD
1920*1080P@60fps, 1280*1024P@60fps, 1280*720P@60fps	Office
Expandable 1280ch@D1 or 320ch@1080P decoding (Optional)	
• Support 1/4/6/8/9/16/25/36 Split Windows	
Support 320ch@1080P H.265 signal decoding (full configured)	
<ul> <li>Support analog/digital video signals input and matrix output</li> </ul>	
Support SD/HD video signal matrix switch and output	
Support non-compressed digital signal encoding output	
6 RJ-45 gigabit network ports for matrix control, preview and online central	
storage.	
Support TCP/IP/RTP/RTSP/RTCP/TCP/UDP/DHCP/PPPoE and etc. network	
protocols	
Remote cast analog/digital video onto the video-wall	
Remote reboot/upgrade/default setting and etc. operations	
Support VGA signal automatic adjustment	
Redundant Power Supply	
Control mode: PC client-end/Local Operate Menu/Network Keyboard/IPAD	
Core i7 7 <sup>th</sup> Gen PC for Software of Video Wall Processor Type Intel core i7 Processor Speed 3.6 GHz RAM size 4GB Hard drive size 1TB	01+01 =02 For HD & MD Office



The Carriero Dinama question A.	Office
120W RMS Mixer Amplifier, 3 mic, 2 aux, 100V/70V and 4ohms High Quality	01+01=02 For HD & MD Office
Desktop Mic High Quality ( with push button to turn on and off )	
High Quality Stereo Amplifier for system	02
Installation, configuration, Testing, Commissioning charges.	01job
Installation, commissioning, Testing of Complete unit in all aspects.	01

Incharge IT Department